



SPECIFICATIONS PAGE

ADVANTAGE LOW PROFILE DUMP DUMP TRAILER



ADVANTAGE LOW PROFILE DUMP STANDARD FEATURES

Adjustable 2-5/16" Ball Coupler or Pintle Ring
Safety Chains
7-Way SAE Plug
Zip Breakaway System
Breakaway Switch
Charge Wire with Circuit Breaker
7K Bolt-On Drop Leg Jack
Double-Acting Tailgate with Chains
Diamond Plate Fenders
EZ Lube Axles
Electric Brake Axles (2)

Slipper Spring Suspension
Silver Wheels
Epoxy Primer
Polyurethane Paint Finish
Spare Tire Mount
Sealed Wiring Harness
LED Lights – Rubber Mounted
Aluminum Lockable Pump Box
Remote Control with 20' Cord
12V Deep-Cycle Battery
Three Year Warranty

Specifications subject to change without notice.





SPECIFICATIONS PAGE

ADVANTAGE LOW PROFILE DUMP DUMP TRAILER

	60" x 10'	72.5" x 10'	72.5" x 10'	72.5" x 12'
Model #	P7510LPDT	P8610LPDT	P10610LPDT	P10612LPDT
GVWR (lb.)	7000	8050	9998	9998
GAWR (lb. / Axle)	4999	3500	4999	4999
Curb Weight	1780	1900	2080	2340
Payload	5220	6150	7918	7658
Frame	5" Channel	6" x 2" x 3/16" Rec. Tube		
Crossmembers	10 Gauge, Formed	3" Channel		
Tongue	5" Channel			
Coupler	Adjustable 2-5/16" Ball Coupler or Pintle Ring			
Jack	7K Bolt-On Drop Leg Jack			
Fenders	Diamond Plate			
Axles	3,500 lb, Greased		5,200 lb, Greased	
Suspension	Slipper Spring Suspension			
Tires	205/75R15 LRC		225/75R15 LRD	
Wheels	15"			
Volume Capacity	3.2 cu yd	3.9 cu yd		4.5 cu yd
Lights	LED Lights - Rubber Mounted			
Electric Plug	7-Way SAE Plug			
Finish	PPG Industrial Polyurethane Paint			
Overall Length	172"			196"
Bed Width Inside	60"	72.5"		
Bed Length Inside	120"			144"
Side Wall Height	20.5"			
Deck Height	26"	28"		
Coupler Height	14" - 22"			
Gate	Double-Acting Tailgate w/ Chains	Triple-Acting Tailgate w/Chains		
Hydraulic Cylinder	One 3.5" x 36"			
Hydraulic Pump	12V Single Acting			
Battery	12V Deep-Cycle Battery			
Dump Angle	48°			46°

Specifications subject to change without notice.

