



SPECIFICATIONS PAGE

ADVANTAGE SINGLE AXLE DUMP DUMP TRAILER



ADVANTAGE SINGLE AXLE DUMP STANDARD FEATURES

Adjustable 2-5/16" Ball Coupler or Pintle Ring
Safety Chains
7-Way SAE Plug
Breakaway Switch
Charge Wire with Circuit Breaker
7K Bolt-On Drop Leg Jack
Double-Acting Tailgate with Chains
Diamond Plate Fenders
EZ Lube Axles
Electric Brakes
Nev-R-Adjust Brakes
Slipper Spring Suspension
Silver Wheels

Epoxy Primer
Polyurethane Paint Finish
10-Gauge Floor
14-Gauge Sides
Spare Tire Mount
2" x 4" Full Height Stake Pockets
Sealed Wiring Harness
LED Lights – Rubber Mounted
Aluminum Lockable Pump Box
Remote Control with 20' Cord
12V Deep-Cycle Battery
Three Year Warranty

Specifications subject to change without notice.





SPECIFICATIONS PAGE

ADVANTAGE SINGLE AXLE DUMP DUMP TRAILER

	60" x 8'
Model #	P5508LPDT
GVWR (lb.)	5000
GAWR (lb. / Axle)	5000
Curb Weight	1250
Payload	3750
Frame	4" Channel
Crossmembers	3" Channel
Tongue	4" Channel
Coupler	Adjustable 2-5/16" Ball Coupler or Pintle Ring
Jack	7K Bolt-On Drop Leg Jack
Fenders	Diamond Plate
Axles	5,000 lb, Greased
Suspension	Slipper Spring Suspension
Tires	225/75R15 LRD
Wheels	15"
Volume Capacity	2.6 cu yd
Lights	LED Lights - Rubber Mounted
Electric Plug	7-Way SAE Plug
Finish	PPG Industrial Polyurethane Paint
Overall Length	147"
Bed Width Inside	60"
Bed Length Inside	96"
Side Wall Height	20.5"
Deck Height	26"
Coupler Height	16" - 24"
Gate	Double-Acting Tailgate w/ Chains
Hydraulic Cylinder	One 3" x 24"
Hydraulic Pump	12V Single Acting
Battery	12V Deep-Cycle Battery
Dump Angle	48°

Specifications subject to change without notice.

