



SPECIFICATIONS PAGE

CHANNEL FRAME EQUIPMENT HAULER



CHANNEL FRAME STANDARD FEATURES

- Adjustable 2-5/16" Ball Coupler or Pintle Ring
- Safety Chains
- 7-Way SAE Plug
- Zip Breakaway System
- 7K Bolt-On Drop Leg Jack (12K on 7 & 8 Ton)
- 5' Quick Release Ramps (Angle or Wood Filled)
- Diamond Plate Fenders
- EZ Lube Axles
- Electric Brake Axles (2)
- Slipper Spring Suspension
- Silver Wheels

- Epoxy Primer
- Polyurethane Paint Finish
- Pressure-Treated Pine Decking (Oak on 8 Ton)
- Spare Tire Mount
- D-Ring Tie Downs - 5/8" (6)
- Stake Pockets (12)
- Aluminum Toolbox
- Sealed Wiring Harness
- LED Lights - Rubber Mounted
- Three Year Warranty

Specifications subject to change without notice.





SPECIFICATIONS PAGE

CHANNEL FRAME EQUIPMENT HAULER

	10K	12K	14K	16K
Model #	P5CAM18C	P6CAM18C	P7CAM18C	P8CAM18C
GVWR (lb.)	11960	13800	16100	18400
GAWR (lb. / Axle)	5080	6000	7000	8000
Curb Weight	2300	2960	3200	3810
Payload	9660	10840	12900	14590
Frame	6" Channel @ 10.5 lb			
Crossmembers	3" Channel			
Tongue	6" Channel @ 8.2 lb			6" Channel @ 10.5 lb
Coupler	Adjustable 2-5/16" Ball Coupler or Pintle Ring			
Jack	7K Bolt-On Drop Leg Jack		12K Bolt-On Drop Leg Jack	
Fenders	Diamond Plate			
Axles	5,200 lbs, Greased	6,000 lb, Greased	7,000 lb, Greased	8,000 lb, Oil Bath
Suspension	Slipper Spring Suspension			
Tires	225/75R15 LRD	235/80R16 LRE		215/75R17.5 LRH
Wheels	15"	16"		17.5"
Decking	Pressure-Treated Pine Decking			Oak Decking
Lights	LED Lights - Rubber Mounted			
Electric Plug	7-Way SAE Plug			
Finish	PPG Industrial Polyurethane Paint			
Overall Length / Flat	268" / 216"			
Deck Width	82.5"	81"		
Deck Height	20"	21"		
Coupler Height	17" -21.5"			
Ramps	5' Quick Release Ramps			

Specifications subject to change without notice.

