

LOW PROFILE HEAVY DUTY DUMP TRAILER



LOW PROFILE HD DUMP STANDARD FEATURES

Tubular Main Frame
 102" Width
 Adjustable 2-5/16" Ball Coupler or Pintle Ring
 Safety Chains
 7-Way SAE Plug
 Breakaway Switch
 Charge Wire with Circuit Breaker
 7K Bolt-On Drop Leg Jack
 Slide-Out Ladder Ramps (6')
 Triple-Acting Tailgate w/ Chains
 Diamond Plate Fenders
 EZ Lube Axles
 Electric Brake Axles (2)
 Nev-R-Adjust Brakes
 Slipper Spring Suspension
 Silver Wheels
 Epoxy Primer

Polyurethane Paint Finish
 10-Gauge Floor
 12-Gauge Sides
 Spare Tire Mount
 D-Ring Tie-Downs - 1/2" (4)
 2" x 4" Full Height Stake Pockets
 Tie Down Rail
 Storage Tray
 Rear Stabilizer Legs
 Sealed Wiring Harness
 LED Lights – Rubber Mounted
 Aluminum Lockable Pump Box
 Remote Control with 20' Cord
 12V Deep-Cycle Battery
 110V Battery Charger
 Three Year Warranty

Specifications subject to change without notice.



SPECIFICATIONS PAGE

LOW PROFILE HEAVY DUTY DUMP TRAILER

	6'x12'	6'x14'	6'x14'	6'x16'	6'x14'	6'x16'
Model #	P6CAM612LPHD	P6CAM614LPHD	P7CAM614LPHD	P7CAM616LPHD	P8CAM614LPHD	P8CAM616LPHD
GVWR (lb.)	13800	13800	16100	16100	18400	18400
GAWR (lb. / Axle)	6000	6000	7000	7000	8000	8000
Curb Weight	3740	4040	4080	4340	5470	5730
Payload	10060	9760	12020	11760	12930	12670
Frame	6" x 3" x 3/16" Rec. Tube			6" x 3" x 1/4" Rec. Tube	6" x 3" x 3/16" Rec. Tube	6" x 3" x 1/4" Rec. Tube
Crossmembers	3" Channel					
Tongue	5" Channel					
Coupler	Adjustable 2-5/16" Ball Coupler or Pintle Ring					
Jack	12K Bolt-On Drop Leg Jack					
Fenders	Diamond Plate					
Axles	6,000 lb, Greased		7,000 lb Greased		8,000 lb, Oil Bath	
Suspension	Slipper Spring Suspension					
Tires	235/80R16 LRE			215/75R17.5 LRH		
Wheels	16"			17.5"		
Volume Capacity	5.16 cu yd	6.02 cu yd	6.02 cu yd	6.87 cu yd	6.3 cu yd	7.2 cu yd
Lights	LED Lights - Rubber Mounted					
Electric Plug	7-Way SAE Plug					
Finish	PPG Industrial Polyurethane Paint					
Overall Length	188"	212"		236"	212"	236"
Bed Width Inside	81.5"					
Bed Length Inside	144"	168"		192"	168"	192"
Side Wall Height	20.5"					
Deck Height	29"	29"	29"	29"	30"	30"
Coupler Height	18.5" - 23"				19.5" - 24"	
Gate	Triple-Acting Tailgate w/Chains					
Hydraulic Cylinders	Two Telescopic Cylinders					
Hydraulic Pump	12V Single Acting					
Battery	12V Deep Cycle Battery					
Dump Angle	46°	45°		43°	45°	43°

Specifications subject to change without notice.

