



## SPECIFICATIONS PAGE

# 12' FULL DECK TILT TRAILER



## 12' FULL DECK TILT STANDARD FEATURES

Adjustable 2-5/16" Ball Coupler or Pintle Ring  
Safety Chains  
7-Way SAE Plug  
Zip Breakaway System  
7K Bolt-On Drop Leg Jack  
Diamond Plate Fenders  
EZ Lube Axles  
Electric Brakes  
Nev-R-Adjust Brakes  
Slipper Spring Suspension  
Silver Wheels

Epoxy Primer  
Polyurethane Paint Finish  
Pressure-Treated Pine Decking  
Spare Tire Mount  
D-Ring Tie-Downs - 5/8" (4)  
Banjo Eye Tie-Downs (2)  
Sealed Wiring Harness  
LED Lights – Rubber Mounted  
Adjustable Hydraulic Cushion Cylinder  
Three Year Warranty

*Specifications subject to change without notice.*





# SPECIFICATIONS PAGE

## 12' FULL DECK TILT TRAILER

	10K	10K	10K
Model #	P5CAM612FTT	P5CAM712FTT	P5CAM714FTT
GVWR (lb.)	11960	11960	11960
GAWR (lb. / Axle)	5080	5080	5080
Curb Weight	2300	2350	2560
Payload	9660	9610	9400
Frame	6"x4"x5/16" Angle		
Crossmembers	3" Channel		
Tongue	6"x4"x5/16" Angle		
Coupler	Adjustable 2-5/16" Ball Coupler or Pintle Ring		
Jack	7K Bolt-On Drop Leg Jack		
Fenders	Diamond Plate		
Axles	5,000 lb, Greased		
Suspension	Slipper Spring Suspension		
Tires	225/75R15 LRD		
Wheels	15" Spoke		
Decking	Pressure-Treated Pine Decking		
Lights	LED Lights - Rubber Mounted		
Electric Plug	7-Way SAE Plug		
Finish	PPG Industrial Polyurethane Paint		
Overall Length	198"		222"
Between Fenders	75"	81"	
Deck Height	16"		
Coupler Height	14" - 20.75"		
Load Angle	11°		10°

Specifications subject to change without notice.

